

(19)



JAPANESE PATENT OFFICE

PATENT ABSTRACTS OF JAPAN

(11) Publication number: **11046186 A**

(43) Date of publication of application: **16.02.99**

(51) Int. Cl

H04L 1/00
H04B 7/26

(21) Application number: **09213945**

(71) Applicant: **CANON INC**

(22) Date of filing: **25.07.97**

(72) Inventor: **AKEBOSHI TOSHIHIKO**
KANDA TETSUO
MORITOMO KAZUO

(54) **COMMUNICATION CONTROL SYSTEM AND
RADIO COMMUNICATION SYSTEM**

it is possible to minimize error occurrences.

COPYRIGHT: (C)1999,JPO

(57) Abstract:

PROBLEM TO BE SOLVED: To minimize the occurrence of errors and to maintain a satisfactory communication quality even at the time of S/N deterioration, by executing predictive processing which predicts a propagation state from a data error occurrence pattern and packet length selection processing which selects optimum packet length based on the predictive result.

SOLUTION: An SS transmitting and receiving part 201 which receives from an antenna 200 performs correlation detection by using a receiving signal and performs a receiving demodulation operation after performing synchronization acquisition based on the correlation value. A signal that is to a self-station among image data which are received by the part 201 is performed error correction in a packet unit by an ECC coding and error correcting part 202 after it is demodulated. In such cases, error information which is acquired by the part 202 is sent to a controlling part 206 to be accumulated. A propagation state is predicted from a data error occurrence pattern and optimum packet length is selected based on the predictive result. With this,

